

OpenSSH on Windows

https://learn.microsoft.com/en-us/windows-server/administration/openssh/openssh_install_firstuse?tabs=gui

Check if OpenSSH is available

```
Get-WindowsCapability -Online | Where-Object Name -like 'OpenSSH*'
```

Install OpenSSH Client and Server

```
# Install the OpenSSH Client
Add-WindowsCapability -Online -Name OpenSSH.Client~~~~0.0.1.0

# Install the OpenSSH Server
Add-WindowsCapability -Online -Name OpenSSH.Server~~~~0.0.1.0
```

Start OpenSSH Server

```
# Start the sshd service
Start-Service sshd
```

Set OpenSSH Server to start automatically on boot

```
# OPTIONAL but recommended:
Set-Service -Name sshd -StartupType 'Automatic'
```

Make sure the firewall doesn't block the OpenSSH Server

```
# Confirm the Firewall rule is configured. It should be created automatically by setup. Run the following to verify
if (!(Get-NetFirewallRule -Name "OpenSSH-Server-In-TCP" -ErrorAction SilentlyContinue | Select-Object Name,
Enabled)) {
    Write-Output "Firewall Rule 'OpenSSH-Server-In-TCP' does not exist, creating it..."
    New-NetFirewallRule -Name 'OpenSSH-Server-In-TCP' -DisplayName 'OpenSSH Server (sshd)' -Enabled True -
Direction Inbound -Protocol TCP -Action Allow -LocalPort 22
} else {
```

```
Write-Output "Firewall rule 'OpenSSH-Server-In-TCP' has been created and exists."
```

```
}
```

Run sshd on an alternate port

Edit the Port line in `C:\ProgramData\ssh\sshd_config`:

```
Port 12322
```

Use the following command to update the Windows Firewall rule to match the port you specified above:

```
Set-NetFirewallRule -Name 'OpenSSH-Server-In-TCP' -LocalPort 12322
```

Require publickey and password authentication

Add the following line to `C:\ProgramData\ssh\sshd_config`

```
AuthenticationMethods "publickey,password"
```

publickey authentication for administrators

Public keys for administrators must be put in the file

`%PROGRAMDATA%\ssh\administrators_authorized_keys`. Use the script below to make sure the file has proper permissions.

```
$acl = Get-Acl C:\ProgramData\ssh\administrators_authorized_keys
$acl.SetAccessRuleProtection($true, $false)
$administratorsRule = New-Object
system.security.accesscontrol.filesystemaccessrule("Administrators","FullControl","Allow")
$systemRule = New-Object system.security.accesscontrol.filesystemaccessrule("SYSTEM","FullControl","Allow")
$acl.SetAccessRule($administratorsRule)
$acl.SetAccessRule($systemRule)
$acl | Set-Acl
```

Stop and Start the sshd service

```
Stop-Service sshd
```

```
Start-Service sshd
```

```
netstat -an -p TCP | find '"22"'
```

Example configuration

Port 12322

```
#PubkeyAuthentication yes
```

```
AuthenticationMethods "publickey,password"
```

```
AuthorizedKeysFile .ssh/authorized_keys
```

```
#PasswordAuthentication yes
```

```
#PermitEmptyPasswords no
```

```
# override default of no subsystems
```

```
Subsystem sftp sftp-server.exe
```

Match Group administrators

```
AuthorizedKeysFile __PROGRAMDATA__/ssh/administrators_authorized_keys
```

Use PowerShell as default interpreter

```
# Check current value of registry key
```

```
Get-ItemProperty -Path "HKLM:\SOFTWARE\OpenSSH" -Name DefaultShell
```

```
# Legacy PowerShell
```

```
New-ItemProperty -Path "HKLM:\SOFTWARE\OpenSSH" -Name DefaultShell -Value
```

```
"C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe" -PropertyType String -Force
```

```
# PowerShell v7
```

```
New-ItemProperty -Path "HKLM:\SOFTWARE\OpenSSH" -Name DefaultShell -Value "C:\Program
```

```
Files\PowerShell\7\pwsh.exe" -PropertyType String -Force
```

```
# Delete registry key to revert to traditional command line
```

```
Remove-ItemProperty -Path "HKLM:\SOFTWARE\OpenSSH" -Name DefaultShell
```

#end

Revision #6

Created 25 June 2023 19:27:22 by bluecrow76

Updated 24 October 2024 22:37:19 by bluecrow76